

# Premier Flagstone Freestanding Safe

## Specification



Cash Rating up to £4,000  
Up to £40,000 Valuables / Jewellery Cover

Traditional Style Safe with Special Composite Infill  
60 Minute Fire Protection for Paper, Tested to 750 °C

Door Fitted with Smoke / Fire Resistant Seal

VDS Class 1 High Security Lock As Standard -  
Electronic or 3 Wheel Combination Lock Available

Live Anti Explosive Device

Anti-drill Plates are Fitted to Resist Attack when the  
Bolts are Locked in Position

Base Fixing - Plus Rear Fixing in Flagstone 0  
(Horizontal & Vertical) & Flagstone 1

3mm Inner Body  
3mm Outer Body  
10mm Door Thickness  
35mm Infill  
2 x 30mm dia. Front Bolts  
2x 30mm dia. Dead Bolts

Freestanding Safes	External (mm)			Internal (mm)			Weight KG
	H	W	D	H	W	D	
Flagstone 0 Horizontal	260	440	370	180	345	250	60
Flagstone 0 Vertical	440	260	370	350	175	245	60
Flagstone 1	405	360	390	320	265	245	75
Flagstone 2	480	430	450	400	345	305	122
Flagstone 3	607	455	455	505	355	330	140
Flagstone Compact	315	390	365	230	305	240	65
Flagstone Jewellery with four flock lined drawers	405	360	390	320	265	245	76

To enable continued product development we reserve the right to alter the specification without notice. All measurements must be considered as approximate.



Made in UK



**Stone Safes Manufacturing Limited**

Unit 8D, Whitebridge Estate, Whitebridge Lane, Stone, Staffordshire ST15 8LQ

Tel / Fax: 01785 812902 Email: [enquiries@stonesafes.co.uk](mailto:enquiries@stonesafes.co.uk)

[www.stonesafes.co.uk](http://www.stonesafes.co.uk)